

CDD10-15

1–1.5T Electric Rider Stacker



SPECIFICATIONS

Model	CDD10								CDD12								CDD15							
Load capacity (kg)	1000								1200								1500							
Load capacity on Max. height(kg)	1000	1000	1000	800	750	700	600	500	1200	1200	1200	950	900	850	750	600	1500	1500	1400	1200	1150	1100	900	700
The max. lifting height(mm)	1600	1800	2000	2600	3000	3200	3600	4000	1600	1800	2000	2600	3000	3200	3600	4000	1600	1800	2000	2600	3000	3200	3600	4000
Load center distance(mm)	600								600								600							
Fork length(mm)	1150								1150								1150							
Single fork width(mm)	180								180								180							
Overall fork width(mm)	570/695								570/695								570/695							
Lowered fork height(mm)	86								86								86							
Fixed leg length(mm)	875								875								875							
Single fixed leg width(mm)	124								124								124							
Inside width between fixed legs(mm)	266/391								266/391								266/391							
Outside width between fixed legs(mm)	514/639								514/639								514/639							
Aisle width for pallets 1000×1200 cross ways(mm)	2232								2232								2232							
Aisle width for pallets 800×1200 length ways(mm)	2302								2302								2302							
Turning radius(mm)	1460								1460								1460							
Front wheel size, number	Φ80*70、4个								Φ80*70、4个								Φ80*70、4个							
Driving wheel size, number	Φ250*80、1个								Φ250*80、1个								Φ250*80、1个							
Balance wheel size, number	Φ150*58、2个								Φ150*58、2个								Φ150*58、2个							
Overall length(with Pedal)(mm)	1914(2314)								1914(2314)								1914(2314)							
Overall width(mm)	808								808								808							
Extended mast height(mm)	2077	2277	2537	3137	3497	3687	4087	4487	2077	2277	2537	3137	3497	3687	4087	4487	2077	2277	2537	3137	3497	3687	4087	4487
Lowered mast height (mm)	2077	2277	1577	1877	2027	2127	2327	2527	2077	2277	1577	1877	2027	2127	2327	2527	2077	2277	1577	1877	2027	2127	2327	2527
Battery voltage(dimensions)mm	24V/210AH (790/210/458)								24V/210AH (790/210/458)								24V/210AH (790/210/458)							
The charger	24V/30A								24V/30A								24V/30A							
Lifting Motor	2.2kw.Lift speed,laden/unladen:130/82mm,Lowering speed,laden/unladen:141/133mm/s																							
Driving Motor	AC;1.5kw.Driving speed,laden/unladen:4.8/4.0km/h																							
Working time of fully charged batteries (h)	5																							
Service Weight(kg)	810	820	890	920	940	960	970	990	820	830	900	930	950	970	980	1000	840	850	900	950	960	980	1000	1020

The company reserves the right to change the parameters without notice.

PRODUCT FEATURES

- 1.Imported AC controller, has stepless speed control,reverse warping function and short circuit protection function;
- 2.Control the emergency reverse switch on the handle,when the vehicle is retracted, prevent the operator from being squeezed;
- 3.Standard the lifting limit function, when the fork rises to the top, the system automatically cuts off the uplink power supply, smooth parking;
- 4.Standard with a high-serving speed limit device, when the door frame is from the bottom. After the distance is raised,the driving speed is automatically reduced, and the operation is improved;
- 5.Operating handle is adding turtle speed switches, low-speed control is more accurate;
- 6.When the door frame falls to the bottom position, the driving speed is automatically accelerated and the work efficiency is improved.



ADDRESS: SHANGHAI ROAD, BAOHE INDUSTRIAL PARK, HEFEI, ANHUI, CHINA PC. 230051

TEL: 86-551-62297986

FAX: 86-551-62297990

WEB: www.jaczg.com ; www.jacforklift.com

E-mail: jac@jaczg.com

All Rights Reserved by JAC heavy duty co.,Ltd. Parameter updating without notice, the picture just for reference. 2023/11/08